

SERIES 6000

FITTING SELECTOR GUIDE

P6510 04-06-V

Thread Type:

 **BLANK = Bare NPTF threads**

 **C = Coated with thread sealant**

 **P = Pro-Fit® with NPTF Thread Advantages:**

- For inch tubing
- Short NPTF thread with PTFE sealing ring
- Eliminates the need for thread sealant
- Faster and cleaner assembly
- Installs flush with no exposed threads
- Fits in NPTF and BSPP ports (1/8", 1/4", and 3/8")

 **S = Sprint® with BSP thread Advantages:**

- For metric tubing
- Short BSP thread with PTFE sealing ring
- Eliminates the need for thread sealant
- Faster and cleaner assembly
- Installs flush with no exposed threads
- Also fits in NPTF ports (1/8", 1/4")

Body Style:*



Tube Size (OD):

Inch
 02 = 1/8"
 53 = 5/32"
04 = 1/4"
 05 = 5/16"
 06 = 3/8"
 08 = 1/2"

Thread Size:

NPTF
 32 = 10-32 UNF
 02 = 1/8"
 04 = 1/4"
06 = 3/8"
 08 = 1/2"

Metric**

3 = 3mm
 4 = 4mm
 5 = 5mm
 6 = 6mm
 8 = 8mm
 10 = 10mm
 12 = 12mm

BSP

M5 = M5
 M7 = M7
 1/8 = G1/8
 1/4 = G1/4
 3/8 = G3/8
 1/2 = G1/2

Seal Material* (Optional)

BLANK = Standard
V = Viton
 EPDM = EPDM
 -50C = Low Temp



Scan the QR code, for our entire product catalog.